



CTX-392 and CTX-393 Multiaction tablets 250g

DESCRIPTION:

Solid compound in tablets, especially thought to make that with its only addition to the water in the swimming pool, you manage to eliminate all the bacteria, viruses and micro-organisms in general. It prevents the weeds development and helps to keep the water clear and transparent .

PROPERTIES:

Appearance	solid in tablets
Colour	White and blue
Available chlorine	76%
pH (1%)	2.5 – 3

CHARACTERISTICS:

According to the labelling regulations on substances and dangerous preparations, the product has a minor danger degree in comparison with the chlorinated comburent products

The non comburent products are safer during its storage in comparison with the chlorinated comburent products

It keeps the same oxidising and disinfectant properties then the chlorinated comburent products.

Product adequate for the swimming pool disinfection built with ceramic materials.

This product can neither be in direct contact with the swimming pools bade with liner, polyester or vinyl, nor with painted swimming pools because it may cause discolorations.

DOSAGE AND INSTRUCTIONS FOR USE:

Initial treatment: Add 15 gram of Dichloroisocyanuric Acid Granules (0200GR) for every m³ water. After 2 hours, adjust the water pH between 7,2 and 7,6 using either Solid pH Reducer (0010) or pH Enhancer (0020).

Maintenance treatment: Once we have the water pH adjusted, add 1 tablet of Eco multiaction tablet (1393) for every 25 m³ water during 7 days.

These doses are the ones suggested and can be modified according to the own characteristics of every swimming pool, climate, etc.

The initial treatment (Superchloring) will have to be repeated whenever you notice a lack of transparency in the water.

Introduce the necessary eco multiaction tablets (1393) doses inside the skimmers. Connect the filtering equipment after and you will have the product dissolved in the water, because water will be flowing through the skimmers.

It is essential that the entire volume of the pool water is recirculated through the scrubber equipment daily.

The residual free chlorine will be between 0.5 and 2 mg/l. This value will easily be measured using an analyser chlorine and pH case. This control will have to be done twice a day minimum.